

## Flexible double-walled aluminium duct pipe



Item	Colour	∅ pipe mm	Length mt
<b>TFLAIS82</b>	aluminium	82	10
<b>TFLAIS102</b>	aluminium	102	10
<b>TFLAIS127</b>	aluminium	127	10
<b>TFLAIS152</b>	aluminium	152	10
<b>TFLAIS160</b>	aluminium	160	10
<b>TFLAIS180</b>	aluminium	180	10

**Description:** Flexible and extensible double-walled anti-noise pipe

**Material:** Aluminium

**Features:** The flexible and extensible anti-noise pipes are double wall insulated and have a class M1 fire resistance, an internal operating temperature ranging from -30°C / +140°C, an external operating temperature ranging from -30°C / +140°C, a max air speed of 30 m / sec, and a max pressure of 2500 Pa.



## Flexible double-walled aluminium duct pipe



Item	Colour	∅ pipe mm	Length mt
<b>TFLAIS204</b>	aluminium	204	10
<b>TFLAIS229</b>	aluminium	229	10
<b>TFLAIS254</b>	aluminium	254	10
<b>TFLAIS305</b>	aluminium	305	10
<b>TFLAIS315</b>	aluminium	315	10

**Description:** Flexible and extensible double-walled anti-noise pipe

**Material:** Aluminium

**Features:** The flexible and extensible anti-noise pipes are double wall insulated and have a class M1 fire resistance, an internal operating temperature ranging from -30°C / +140°C, an external operating temperature ranging from -30°C / +140°C, a max air speed of 30 m / sec, and a max pressure of 2500 Pa.

